

MYG 无刷三相交流同步发电机系列

型号	常用功率 (KW/KVA)	额定电压 (V)	额定电流 (A)	功率因数 (cos φ)	额定转速 (r/min)	稳态电压调整率 (%)
MYG-5	5/6.25	400/230	9	0.8	1500	±1
MYG-7.5	7.5/9.375	400/230	13.5	0.8	1500	±1
MYG-10	10/12.5	400/230	18.1	0.8	1500	±1
MYG-12	12/15	400/230	21.6	0.8	1500	±1
MYG-13	13/16.25	400/230	23.5	0.8	1500	±1
MYG-15	15/18.75	400/230	27.1	0.8	1500	±1
MYG-16	16/20	400/230	28.8	0.8	1500	±1
MYG-18	18/22.5	400/230	32.5	0.8	1500	±1
MYG-20	20/25	400/230	36.1	0.8	1500	±1
MYG-22	22/27.5	400/230	39.7	0.8	1500	±1
MYG-24	24/30	400/230	43.2	0.8	1500	±1
MYG-25	25/31.25	400/230	45.1	0.8	1500	±1
MYG-30	30/37.5	400/230	54.1	0.8	1500	±1
MYG-34	34/42.5	400/230	61.3	0.8	1500	±1
MYG-40	40/50	400/230	72.2	0.8	1500	±1
MYG-50	50/62.5	400/230	90.2	0.8	1500	±1