

DIESEL GENERATOR SET TECHNICAL DATA

MINYUAN GENERATOR SET MODEL	GF-DC200	
	Prime output	Standby output
Generator power (KW)	160	180
Generator power (KVA)	200	225
Max.Engine power (KW)	203	
Engine Model	6CTAA8.3-G2	
Manufacturer	CUMMINS DCEC	
Cylinder Arrangement	6 in line	
Cooling System	Water-cooled, radiator 40°C max, fans are driven by belt, with safety guard	
Governor Type	Electronic	
Starting System	24V one way start	
Engine Filter	Dry type air filter, fuel filter, oil filter	
Fuel System	A type fuel pump	
Displacement (L)	8.3	
Compression Ratio	16.0:1	
Rated RPM	1500	
Bore and Stroke (mm)	114x135	
100% (Prime power)load (L/h)	32.8	36.08
Air Flow (m ³ /s)	300	
Burning Capacity (m ³ /s)	11.2	
Exhaust Gas Flow (m ³ /s)	29.1	
Exhaust Temperature (°C)	545	
Total Oil Capacity (L)	24	
Total Coolant Capacity (L)	40	
Alternator model	MYG -160	
Manufacturer	MINYUAN	
Opening switch	MCCB Air switch	
Rated voltage/frequency	400/230V; 50Hz	
Voltage Adjust range	< 5%	
Voltage Regulation	≥ 95% - 105%	
Voltage Regulation, Steady State	< ±1%	
Exciter Type	Brushless, self-exciting	
Insulation Class/Protection Grade	Class H/IP23	
Efect factor of telecom TIF/THF	TIF<50/THF<2%	
Connecting type	3 phase and 4 wires, "Y" type connecting	
Random accessories	Battery, battery's cable, Ripple flex exhaust, exhaust siphon, flange	
Open type - Overall size (mm)	2540x950x1630	
Weight (kg)	1900	
Soundproof type - Overall size (mm)	3590x1250x2050	
Weight (kg)	2750	