

DIESEL GENERATOR SET TECHNICAL DATA

MINYUAN GENERATOR SET MODEL	GF-DC60	
	Prime output	Standby output
Generator power (KW)	48	52
Generator power (KVA)	60	65
Max.Engine power (KW)	65	
Engine Model	4BTA3.9-G2	
Manufacturer	CUMMINS DCEC	
Cylinder Arrangement	4 in line	
Cooling System	Water-cooled, radiator 40 °C max, fans are driven by belt, with safety guard	
Governor Type	Electronic	
Starting System	24V one way start	
Engine Filter	Dry type air filter, fuel filter, oil filter	
Fuel System	A type fuel pump	
Displacement (L)	3.9	
Compression Ratio	16.5:1	
Rated RPM	1500	
Bore and Stroke (mm)	102x120	
100% (Prime power)load (L/h)	10.36	11.23
Air Flow (m ³ /s)	158	
Burning Capacity (m ³ /s)	5.9	
Exhaust Gas Flow (m ³ /s)	14.8	
Exhaust Temperature (°C)	497	
Total Oil Capacity (L)	16.4	
Total Coolant Capacity (L)	24	
Alternator model	MYG - 48	
Manufacturer	MINYUAN	
Opening switch	MCCB Air switch	
Rated voltage/frequency	400/230V; 50Hz	
Voltage Adjust range	< 5%	
Voltage Regulation	≥ 95% - 105%	
Voltage Regulation, Steady State	< ±1%	
Exciter Type	Brushless, self-exciting	
Insulation Class/Protection Grade	Class H/IP23	
Efect factor of telecom TIF/THF	TIF<50/THF<2%	
Connecting type	3 phase and 4 wires, "Y" type connecting	
Random accessories	Battery, battery's cable, Ripple flex exhaust, exhaust siphon, flange	
Open type - Overall size (mm)	1800x750x1450	
Weight (kg)	930	
Soundproof type - Overall size (mm)	2380x1060x1680	
Weight (kg)	1450	

Note: Specifications may change without notice