

Động cơ điện vô nhôm điện dung 1 pha

Type 型号	Power 功率		Voltage 电压 (V)	Current 电流 (A)	Speed 转速 (r/min)	Eff 效率 (%)	Power factor 功率因数	Tst/Tn 堵转转矩 额定转矩	Tmax/Tn 最大转矩 额定转矩	Starting current 起动电流(A)	Net weight 净重 (kg)
	HP	KW									
ML631-2	0.25	0.18	220	1.43	2800	60	0.92	1.8	1.8	7.8	5.3
ML632-2	0.34	0.25	220	1.91	2800	63	0.92	1.8	1.8	10.8	5.6
ML711-2	0.5	0.37	220	2.73	2800	67	0.92	2.3	1.8	16	7
ML712-2	0.75	0.55	220	3.88	2800	70	0.92	2.5	1.8	21	8
ML801-2	1	0.75	220	5.15	2800	72	0.92	2.5	1.8	30	8.5
ML802-2	1.5	1.1	220	7.02	2800	75	0.95	2.5	1.8	40	9.5
ML90S-2	2	1.5	220	9.44	2800	76	0.95	2.5	1.8	55	12.5
ML90L-2	3	2.2	220	13.67	2800	77	0.95	2.5	1.8	80	14
ML100L-2	4	3	220	18.2	2800	79	0.95	2.5	1.8	110	20.5
ML112M-2	5.5	4	220	22.5	2800	78	0.95	2.5	1.8	146	32
ML631-4	0.16	0.12	220	1.24	1400	55	0.90	1.8	1.8	5.7	5.3
ML632-4	0.25	0.18	220	1.43	1400	56	0.90	1.8	1.8	8.64	5.5
ML711-4	0.34	0.25	220	1.99	1400	62	0.92	2.5	1.8	12	6.9
ML712-4	0.5	0.37	220	2.81	1400	65	0.92	2.5	1.8	16	8.1
ML801-4	0.75	0.55	220	4.0	1400	68	0.92	2.5	1.8	21	8.9
ML802-4	1	0.75	220	5.22	1400	71	0.92	2.5	1.8	30	9.6
ML90S-4	1.5	1.1	220	7.2	1400	73	0.95	2.5	1.8	40	13
ML90L-4	2	1.5	220	9.57	1400	75	0.95	2.5	1.8	55	16
ML100L1-4	3	2.2	220	13.9	1400	76	0.95	2.5	1.8	80	23
ML100L2-4	4	3	220	18.6	1400	77	0.95	2.5	1.8	110	27
ML112M-4	5.5	4	220	22	1400	79	0.95	2.5	1.8	146	35