

DIESEL GENERATOR SET TECHNICAL DATA

MINYUAN GENERATOR SET MODEL	GF-CC880	
	Prime output	Standby output
Generator power (KW)	800	880
Generator power (KVA)	1000	1100
Max.Engine power (KW)	970	
Engine Model	KTA38-G5	
Manufacturer	CUMMINS CCEC	
Cylinder Arrangement	12 in "V" type	
Cooling System	Water-cooled, radiator 40 °C max, fans are driven by belt, with safety guard	
Governor Type	Electronic	
Starting System	24V one way start	
Engine Filter	Dry type air filter, fuel filter, oil filter	
Fuel System	A type fuel pump	
Displacement (L)	37.8	
Compression Ratio	13.9:1	
Rated RPM	1500	
Bore and Stroke (mm)	159x159	
100% (Prime power)load (L/h)	161.6	177.76
Air Flow (m ³ /s)	30425	
Burning Capacity (m ³ /s)	1213	
Exhaust Gas Flow (m ³ /s)	3306	
Exhaust Temperature (°C)	513	
Total Oil Capacity (L)	135	
Total Coolant Capacity (L)	258	
Alternator model	TFW - 880	
Manufacturer	MINYUAN	
Opening switch	MCCB Air switch	
Rated voltage/frequency	400/230V; 50Hz	
Voltage Adjust range	< 5%	
Voltage Regulation	≥ 95% - 105%	
Voltage Regulation, Steady State	< ±1%	
Exciter Type	Brushless, self-exciting	
Insulation Class/Protection Grade	Class H/IP23	
Efect factor of telecom TIF/THF	TIF<50/THF<2%	
Connecting type	3 phase and 4 wires, "Y" type connecting	
Random accessories	Battery, battery's cable, Ripple flex exhaust, exhaust siphon, flange	
Open type - Overall size (mm)	4800x2060x2450	
Weight (kg)	7500	
Soundproof type - Overall size (mm)	6058x2438x2896	
Weight (kg)	12500	

Note: Specifications may change without notice